



RM2 - TOP BOX FITTING KIT (REAR RACK) - FITTING INSTRUCTIONS


Maeving top box fitting kit (Rear rack)

These instructions cover the fitting of the top box to the Maeving rear rack using the 'Top box fitting kit (rear rack)'.

Tools required: T30 Torx™.

Top box fitting kit (rear rack) parts supplied:

1.	Mount plate	1 off
2.	Fixing, M6 x 30 mm, T30,	4 off
3.	Washer	4 off
4.	Nuts	4 off



WARNING: The maximum safe carrying capacity for the top box is 3 kg. Never overload the top box, as this could cause the motorcycle to become unstable, leading to loss of control and could result in an accident, causing injury or death.

NOTICE: The maximum safe carrying capacity for the top box is 3 kg. Never overload the top box, as this could cause damage to the motorcycle and accessories.

WARNING: Evenly distribute the load within the top box and pack heavy items towards the bottom. Ensure that items are packed so that they will remain in place and will not shift while the motorcycle is moving. Incorrect loading may result in an unsafe riding condition, which may result in loss of motorcycle control and an accident causing injury or death.

WARNING: Throughout the fitting process, ensure that the motorcycle is stabilised and fully supported by the side stand to prevent risk of injury from the motorcycle falling.

WARNING: A torque wrench of known accurate calibration must be used when fitting this accessory kit. Failure to tighten any of the fasteners to the correct torque specification may cause instability leading to loss of control and could result in an accident, causing injury or death.


Note: Make sure the motorcycle is in a clean and well-lit environment and lay out all the required parts needed to fit the accessory kit to your motorcycle before commencing the installation of the accessory kit.

Note: Read all of the information in these fitting instructions and fully understand the installation process before attempting to fit this accessory kit.


WARNING: The use of the top box will result in the motorcycle exhibiting new handling characteristics that must be allowed for. Failure to do so may cause instability leading to loss of control and could result in an accident, causing injury or death.

Installing the top box fitting kit (rear rack)


1. If you have not already fitted the Maeving rear rack (1) to your motorcycle, you must follow the rear rack fitting instructions before proceeding any further.



2. Align the mount plate with the rear rack. Fit the 4 washers (2), and 4 fixings (3) M6 x 30 mm, to secure the mount plate into position.






3. Position the 4 nuts (3) under the rear rack between the bars and thread the 4 fixings into the nuts. Once in position, tighten the 4 fixings to **8 Nm**.






Top Box Fitting Kit (Rear Rack)

Installing the top box to the rear rack

1. Insert the key in the top box lock (1) and turn to the **UNLOCKED** position.




2. To fit the top box, align the top box so that the mounting tabs on the bottom of the top box (A) locate with the mounting slots on the mount plate (B).



3. Push the top box forwards (1) into the mounting slots and lower the rear of the top box (2) down until the locking mechanism in the base of the top box engages with the top box latch (C).


4. An audible click can be heard when the locking mechanism in the base of the top box is correctly latched in place. Finally, turn the key to the locked position and remove the key.




WARNING: Before riding, always ensure that the top box is mounted correctly and fully secured. A loose or detached top box could cause loss of motorcycle control and an accident causing injury or death.

Removing the top box from the rear rack

1. To remove the top box from the rear rack, insert the key in the lock and turn the key to the **UNLOCKED** position.
2. Press the button below the lock on the top box (**1**), this will release the top box from the rear rack.




3. Lift the rear of the top box up (**1**) away from the latch and then move the top box back (**2**) to release the front mounting tabs from the mounting slots on the mounting plate.



Opening the top box lid

1. To open the top box lid, turn the key to the **UNLOCKED** position and press the button above the lock on the top box.



 Always ensure the lock is returned to the **LOCKED** position once the top box lid is closed.

www.maeving.com

For general enquiries in the UK, please email the
Maeving Support Team at: support@maeving.com

© Maeving Limited.

This publication, or any part thereof, may not be reproduced, copied or
translated without the sole permission of Maeving.

Published: December 2025 - UK Version 1.

For the latest version of these instructions, please visit: www.maeving.com.

Produced by Illston Authoring Limited.

For more information visit www.illstonauthoring.com.